

# ACR46GLCAL



31.5" x 19.5" x 22.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, with stainless steel trimmed glass door, frost-free with an internal fan, external digital controls and NIST-calibrated thermometer, and lock

## Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC/VFA vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

## Product Features:

|                                              |                                                                                                                                                                                                                                                 |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Vaccine refrigerator                         | Purpose-built to meet the recommendations of the CDC, VFC and VFA for reliable vaccine storage                                                                                                                                                  |
| ADA compliant                                | Sized just under 32" high to allow installation under lower ADA compliant counters                                                                                                                                                              |
| Built-in capable                             | Front-breathing system allows the unit to be installed under cabinets with minimum clearance                                                                                                                                                    |
| Slim 20" width                               | Full 2.65 cu.ft. capacity inside conveniently slim footprint                                                                                                                                                                                    |
| High/low temperature alarm                   | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                                                                                                |
| NIST calibrated external temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button                                                                     |
| Certificate of calibration included          | Calibrated to NIST standards in our ISO/IEC 17025:2017 accredited laboratory, with a certificate included for your records                                                                                                                      |
| Digital thermostat                           | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience                                                                                                                  |
| Buffered temperature probe                   | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |

## ACR46GLCAL Specifications:

| Overview                   |                       |
|----------------------------|-----------------------|
| Nominal Height             | 32.0" (81 cm)         |
| Height of Cabinet          | 31.5" (80 cm)         |
| Nominal Width              | 20.0" (51 cm)         |
| Width                      | 19.5" (50 cm)         |
| Nominal Depth              | 23.0" (58 cm)         |
| Depth                      | 22.75" (58 cm)        |
| Depth with Handle          | 25.0" (64 cm)         |
| Depth with door at 90°     | 41.0" (104 cm)        |
| Capacity                   | 2.65 cu.ft. (75 L)    |
| Defrost Type               | Frost-Free            |
| Door                       | Glass/SS              |
| Cabinet                    | White                 |
| US Electrical Safety       | ETL                   |
| Canadian Electrical Safety | ETL-C                 |
| Amps                       | 1.0                   |
| Voltage/Frequency          | 115 V AC/60 Hz        |
| Weight                     | 89.0 lbs. (40 kg)     |
| Parts & Labor Warranty     | 1 Year                |
| Compressor Warranty        | 5 Years               |
| UPC                        | 761101083902          |
| Refrigerator Features      |                       |
| Door Swing                 | RHD                   |
| Reversible                 | Yes                   |
| Shelf Type                 | Wire                  |
| Shelf Qty                  | 3                     |
| Adjustable Shelves         | Yes                   |
| Thermostat Type            | Digital               |
| Fan Type                   | Interior and Exterior |
| Refrigerant Type           | R600a                 |
| Refrigerant Amount         | 0.99oz.               |
| High Side PSI              | 270.0                 |
| Low Side PSI               | 105.0                 |
| Level Legs Qty             | 4                     |
| Interior Light             | Yes                   |
| Temperature Range          | 2° to 8°C             |
| Dimensions                 |                       |
| Interior Height            | 21.25" (54 cm)        |

|                        |                |
|------------------------|----------------|
| Interior Width         | 15.0" (38 cm)  |
| Interior Depth         | 16.13" (41 cm) |
| Compressor Step Height | 3.5" (9 cm)    |
| Compressor Step Width  | 15.0" (38 cm)  |
| Compressor Step Depth  | 4.75" (12 cm)  |

