accucold

AGP96RFLCAL



56.63" x 21.5" x 21.75" (H x W x D)

General purpose refrigerator-freezer with digital refrigerator control, internal fan, combination lock, and NIST calibrated alarm/thermometer

Highlights:

Factory-installed combination lock secures both sections for reliable security

Combination refrigerator-freezer for general purpose storage in facilities

Digital controls allow you easily manage the refrigerator temperature between 2 and 8°C

Product Features:

Refrigerator-freezer combination	2 to 8°C refrigerator section for basic storage applications, with an upper freezer compartment ideal for ice packs	
Combination lock	Factory-installed front lock secures both compartments with a user-set code. Two keys are included to override the combination as needed	
Digital thermostat (refrigerator)	Easy operation with a factory-installed digital thermostat that allows you to manage the refrigerator temperature between 2 and 8°F (NOTE: the freezer temperature will self-adjust based on the refrigerator setting)	
Alarm/thermometer included	Temperature monitoring device (TMD) displays the current and min/max temperature of the refrigerator interior, with an audible alarm to alert if the unit goes out of range	
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle to better simulate the temperature of stored contents instead of refrigerator air temperature	
NIST calibrated external temperature rea	adoutThermometer is NIST calibrated in our ISO/IEC 17025:2017 accredited laboratory and ships with a 2-year certificate of calibration for your records	
Fan-forced cooling	Refrigerator section includes a factory-installed fan to help ensure a more evenly cooled interior	
Automatic defrost refrigerator	Lower refrigerated section does not require manual defrosting	
SUMMIT APPLIANCE DIVISION, FELIX STO Maguaisdeávæstiárbezerny 10474 USA TEL 7	DRCH, INC. ISO 9001:2015 Certified 718-89 Stablic Gaaling-systems in the up fracter compariance.com	

accucold

AGP96RFLCAL Specifications:

Overview	
Nominal Width	22.0" (56 cm)
Nominal Depth	22.0" (56 cm)
Nominal Height	58.0" (147 cm)
Height of Cabinet	58.0" (147 cm)
Height to Hinge Cap	56.63" (144 cm)
Width	21.5" (55 cm)
Width with Door Open	22.25" (57 cm)
Depth	21.75" (55 cm)
Depth with door at 90°	41.5" (105 cm)
Capacity	7.1 cu.ft. (201 L)
Defrost Type	Cycle
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.54
Voltage/Frequency	115 V AC/60 Hz
Weight	105.0 lbs. (48 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101086002
Refrigerator-Freezer	
Door Swing	RHD
Reversible	Yes
Adjustable Shelves	Yes
Interior Light	Yes
Refrigerator - Interior Height	36.5" (93 cm)
Refrigerator - Interior Width	17.5" (44 cm)
Refrigerator - Interior Depth	17.0" (43 cm)
Refrigerator - Shelf Type	Wire
Refrigerator - Shelf Qty	2
Refrigerator - Full Door Shelves	3
Refrigerator - Temperature Range	2 to 8°C
Freezer - Interior Height	10.38" (26 cm)

Freezer - Interior Width	15.5" (39 cm)
Freezer - Interior Depth	16.0" (41 cm)
Freezer - Shelf Type	Wire
Freezer - Shelf Qty	1
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.62 oz.
High Side PSI	245.0
Low Side PSI	110.0
Level Legs	2





SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

