SUMMIT

BIM18IFADA



31.38" x 17.75" x 24" (H x W x D)

18" wide frost-free icemaker in for built-in or freestanding use under ADA compliant counters, with panel-ready door and black cabinet

Highlights:

32" height for installation under lower ADA compliant counters

Produces and stores up to 8 lbs. of crescent ice cubes in a removable bin

Panel-ready door frame allows you to create a truly custom look under the counter

Product Features:

| ADA compliant | Sized just under 32" high for installation under lower ADA compliant counters |
|---------------------------|--|
| Integrated door frame | Stainless steel door frame accepts full overlay panels for users to create a seamless custom look (panel size: 17 1/2" W x 27 3/4" H; maximum weight: 10 lbs.) |
| Built-in capable | Make the best use of space by installing your appliance under the counter |
| No pump or drain required | Convenient design allows more flexibility in positioning the unit |
| Ice production | Makes and stores up to 8 lbs. of crescent cubes |
| Removable bin | Bucket can be removed for fast and easy cleaning |
| Digital thermostat | Electronic controls for precise temperature management. |
| Digital display | Temperature readout can be shown in Celsius or Fahrenheit |
| Frost-free operation | Eliminates the need to manually defrost the interior |







BIM18IFADA Specifications:

| 32.0" (81 cm) | |
|--|--|
| 31.38" (80 cm) | |
| 18.0" (46 cm) | |
| 17.75" (45 cm) | |
| 24.0" (61 cm) | |
| 24.0" (61 cm) | |
| 25.75" (65 cm) | |
| 40.0" (102 cm) | |
| 2.7 cu.ft. (76 L) | |
| Frost-Free | |
| Panel-Ready | |
| Black | |
| ETL | |
| ETL-C | |
| 1.1 | |
| 115 V AC/60 Hz | |
| | |
| 82.0 lbs. (37 kg) | |
| 82.0 lbs. (37 kg) 1 Year | |
| | |
| 1 Year | |
| 1 Year 5 Years | |
| 1 Year 5 Years | |
| 1 Year 5 Years 761101063751 | |
| 1 Year 5 Years 761101063751 RHD | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and Exterior | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and Exterior R600a | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and Exterior R600a 1.06 oz. | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and Exterior R600a 1.06 oz. 270.0 | |
| 1 Year 5 Years 761101063751 RHD Factory Reversible 8.0 lbs. (4 kg) 8.0 lbs. (4 kg) Crescent 1 Yes Interior and Exterior R600a 1.06 oz. 270.0 103.0 | |
| | |

| Compressor Step Height | 4.5" (11 cm) |
|------------------------|----------------|
| Compressor Step Width | 12.75" (32 cm) |
| Compressor Step Depth | 4.5" (11 cm) |
| Level Legs | 4 |
| Temperature Range | -22 to 14ºF |



