


Classic style and superior performance make this chimney range hood the perfect addition to any kitchen. Quiet operation and bright LED lighting enhances your cooking experience, while the sleek 4-speed capacitive touch control makes operation and clean-up easy. An optional remote allows for convenient control from anywhere in the kitchen.

- Ultra-quiet 640 MAX Blower CFM operates at best-in-class < 0.3 sones at normal speed.
- Bright 2-level LED modules (included).
- Tap-touch, four-speed capacitive control features a smooth, easy-to-clean surface.
- Dishwasher-safe hybrid baffle filters feature a quick-release latch for easy removal.
- CRT provides the ability to meet codes and reduce airflow to 300 or 400 CFM.

- 15 minute delay-off function keeps hood running after cooking to ensure smoke and odors have cleared the environment.
- Optional non-duct recirculation kit and filters available.
- Ducted/non-ducted telescopic flue extension accommodates 8' to 9' ceiling heights. Flue extensions available to accommodate ceiling heights from 9' to 10'.
- Installation brackets are included for easy installation.



Optional HCR4 Remote Control.



SPECIFICATIONS							OPTIONAL ACCESSORIES		
Width	MAX Blower CFM*	Blower	Sones <sup>†</sup>	Volts	Amps	Duct	10' Flue Extension	Non-duct Kit	Non-duct Replacement Filter
30" 36"	640	Internal	<0.3	120	3.7	6" RD	FXN58SS	ARKBWP	S99010494

<sup>\*</sup> MAX Blower CFM indicates hood blower performance in open air. Find HVI rated performance for this model in the product specification sheet at Broan-NuTone.com <sup>†</sup> Sones at normal (or working) speed.

Install the hood so that the bottom of the unit is 26" to 36" above the cooking surface. Mounting height may be affected by ceiling height.







