30" TOUCH CONTROL SINGLE OVEN - BLACK GLASS







Interior Lighting

OVEN

Creactive Touch Control System

Dual True Convection

Self-cleaning oven with Multifunction baking

Black Porcelain enamel interior

Cool to the touch

Extra-large baking cavity and viewing area

3 Halogen lights for flawless visibility

Total capacity 123 lt

Total capacity 4,34 cu. ft.

2 chromed racks

1 telescopic rack

Enameled Broiler Pan

Lock Keys Door Lock

OVEN FUNCTIONS

Bake (cooking group)

Broil

Convection (cooking group)

Keep Warm (cooking group)

Classic Pizza Function 590°F

Preset default temperature

Preheat (display instantaneous temperature)

Fast Preheat Mode

Sabbath Mode

Setting Temperature °C/°F

Setting Weight Kg/lb

Event Logs (for Service)

Meat Probe

Self-Clean

OPTIONAL ACCESSORIES

FMTR630


30" Telesc. Rack

fulgor-milano.us **FULGOR** MILANO

DISTINTO

30" TOUCH CONTROL SINGLE OVEN





| CODE ID | 30" TOUCH CONTROL SINGLE OVEN F7SP30B1 700 | | |
|---|--|---|--|
| Series | | | |
| Finish | Black Glass | | |
| CONTROL PANEL | | | |
| Control Type | Creactive Electronic Touch Control | | |
| Display: Clock - Temperature - Function | TFT | TFT 3.5" | |
| Language | English (USA) / English (UK) / Fre | ench / Spanish / Italian / German | |
| | Control Interface | Chime Volume Setting | |
| | Full Touch: Functions - Recipes - Settings Menu | Date Format | |
| | Brightness Setting | Demo Mode | |
| OVEN | | | |
| Туре | Dual True Convection | | |
| Temperature Regulation | Electronic Control (min/max 170/550°F - 75/290°C) | | |
| OVEN FUNCTIONS | | | |
| _ | Pyrolytic Self-Clean | Broil | |
| | True Convection | Dehydrate | |
| | Convection Broil | Thaw (Defrost) | |
| | Convection Roast | Proof (Warm) | |
| | Pizza (Lower Convection) | Keep warm (Warm Plus) | |
| ELECTRIC OVEN EETHER | Bake | Oven Lights | |
| ELECTRIC OVEN FEATURES | Dunc st. staffer th. to see a seed | Display instantaneous townt | |
| | Preset default temperature Child Door Lock | Display instantaneous temperature Control Display Lock | |
| - | Sabbath Mode | 12/24 Hour Clock Formats | |
| - | | Temperature Display °C/°F | |
| - | Automatic Fast Preheat | Event Logs (for Service) | |
| OVEN DOOR(S) | Meat Probe | Event Logs (for Service) | |
| Oven Glass Window | Large See Through Glass | | |
| Door Cooling System | 4 Heat Resistant Glasses | | |
| Door Hinges | Heavy Duty Steady Tilt | | |
| OVEN CAVITY | Heavy Duty Steady Till | | |
| Total Capacity (It) | 123 | | |
| Total Capacity (cu. ft.) | 4,34 | | |
| Cavity Enamel Colour | Black | | |
| Rack Positions | 6 | | |
| Oven Lights | 3x20W Halogen | | |
| HEATING ELEMENTS (@240V) | | - | |
| Broil Upper Heating Element | 3500 W | | |
| Upper Auxiliary Element | 1032 W | | |
| Concealed Bake Lower Heating Element | 3000 W | | |
| Convection Element | 2 x 1300 W | | |
| OVEN ACCESSORIES | | | |
| Chromed Racks | 2 | | |
| Enameled Broiler Pan (basin + anti splash) | 1 | | |
| Telescopic Chromed Rack | 1 | | |
| DIMENSIONS/WEIGHT | | | |
| Overall dim - Width | 29 - 11/16" | (754 mm) | |
| Overall dim - Height | 27 - 7/8" | (707 mm) | |
| Overall dim - Depth | 24" | (610 mm) | |
| Cut-out - Width | 28 - 7/16" | (722 mm) | |
| Cut-out - Height (min) Cut-out - Depth (min) | 27 - 3/8" 23 - 1/4" | (695 mm) | |
| 1 \ / | | (590 mm) | |
| Gross Weight POWER / RATINGS (208/240 V, 60 HZ) | 183 lbs | (83 kg) | |
| kW / Amps rating at 120-240 V, 60 Hz | 2 70141 | - 15 AA | |
| kW / Amps rating at 120-240V, 60Hz | 3.70kW - 15.4A 3.50kW - 16.8A | | |
| Power Cable | 3.5UKW - 16.8A Conduit | | |
| INSTRUCTIONS FOR USE | Con | uuit | |
| Use & Care Manual / Installation Manual | English / French / Spanish | | |
| OSE α Care Manual / Installation Manual | English / French / Spanish | | |

fulgor-milano.us FULGOR MILANO