

# **BUILT-IN 42"W. SIDE-BY-SIDE**

Viking 5 Series - FDSB

#### PROCHILL TEMPERATURE MANAGEMENT SYSTEM

- ENERGY STAR Qualified
- Variable Speed DC Overdrive<sup>™</sup> Compressor quickly chills food and saves energy
- Single compressor system is one of the quietest, most technologically advanced compressors available
- Electronic controls maintain even temperatures within one degree °F to keep food fresher longer
- Odor Eliminator<sup>™</sup> Evaporator removes odors and excess humidity
- Maintenance-free Super Clog Resistant<sup>™</sup> Condenser prevents dust and other airborne particles from clogging the condenser

#### FILTER-FREE FRESHNESS

- EXCLUSIVE Plasmacluster<sup>™</sup> Ion Air Purifier uses advanced ion technology to eliminate airborne bacteria, mold, and odors to enhance food preservation
- Functions at 100% capacity and never degrades, never needs replacing, and no maintenance is ever required

#### LED LIGHTING

- All items are in clear view with bright energy efficient *LED lighting* from top and sidewalls
- Ramp on theater lighting provides better visibility

#### SPECIALIZED REFRIGERATION STORAGE

- One adjustable Humidity Zone<sup>™</sup> Drawer with NEW soft-close slides
  - Humidity can be set high for leafy greens or low for fruits and vegetables with skins
- Additional space for large pizza box storage
- Four deli drawers with soft-close slides
- Two in-the-door dairy compartments with covers
- Four Patented (three are adjustable) aluminum door bins securely store heavy items
- Seamless glass shelves make cleanup easy and maximize usable space
- Adjustable door stops 90, 110 and 120 degrees

#### SPECIALIZED FREEZER STORAGE

- Three adjustable wire shelves for custom storage
- Two slide-out, large capacity wire baskets provide easy storage viewing



- Three patented adjustable aluminum door bins
- Adaptive defrost controls the timing of the defrost periods, instead of an electromechanical defrost timer
  - Extends to 96 hours improves food storage because the unit defrosts less often
- Factory-installed automatic ice maker features *large-capacity* ice bucket
- Door alarm sounds and glows to warn that fresh food door and/ or freezer drawer have been ajar for three minutes, and that the temperature has risen above normal operating range

#### MODEL NUMBERS

 FDSB5424 – 42"W. Side-by-Side Refrigerator/Freezer – Custom Panel

#### ACCESSORIES

 PHK28-SS Professional stainless steel handle (1 piece/28")

#### **DESIGN OPTION**

 Custom panel model (FDSB) available to blend seamlessly into cabinetry with locally supplied front panels

#### WARRANTY

- 2-year full covers complete unit
- 6-year full sealed refrigeration system
- 90-day full cosmetic parts such as glass, painted items, and decorative items
- 12-year limited sealed refrigeration system



## **BUILT-IN 42"W. SIDE-BY-SIDE**

(106.7 cm)

29-3/16" (74.1 cm)

3~19/32" (9.1 cm)

75-15/16" (192.9 cm)

ł

 $\Box$ 

e

41" (104.1 cm)

### Viking 5 Series - FDSB

▲1-1/2" (3.8 cm)

> 9-5/32" (23.3

82-3/4

23.7/8' (60.6 cm) 24-5/8" 4-1/16

42"W. SIDE-BY-SIDE FLUSH MOUNT TRIM AND CUSTOM DOOR OVERLAY	
DESCRIPTION	FDSB5424
Overall Width	42" (106.7 cm)
Overall Height from bottom	82-3/4" (210.2 cm) min. to 84-1/16" (213.5 cm) max.
Overall Depth from rear	To front edge of side trim: 25-1/2" (64.8) To front of top grille: 26-1/4" (66.7 cm) To front of handle endcap: 29-3/16" (74.1 cm)
Cutout Width	42" (106.7 cm)
Cutout Height	82-7/8" (210.5 cm) min. to 84-1/16" (213.5 cm) max.
Flush Mount Cutout depth	26-3/8" (67.0 cm) min.
Electrical Requirements	115 volt, 60 Hz, 15 amp dedicated circuit; 3-wire cord with grounded 3-prong plug attached to product
Maximum Amp Usage	9.9 amps
Inlet Water Requirements	1/4" copper tubing inlet waterline; minimum 20 psi; maximum 120 psi
Overall Interior Dimensions Refrigerator Freezer Total Capacity	15.76 cu. ft. (446 liters) 9.56 cu. ft. (271 liters) 25.32 cu. ft. (717 liters)
Approximate Shipping Weight	559 lb. (254 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/ installation information.



 $^{\odot}$  2025 Viking Range, LLC All rights reserved. Specifications subject to change without notice.