

CODEID

PANEL READY FRENCH DOOR REFRIGERATOR



FM4FBM36IFBI



LED Lighting



Total No Frost



Noise Level 41 (dB)



Integrated Installation



Active Cooling



Deep Freezing



Interior Water Dispenser



Automatic Ice Maker

SPECIFICATIONS

Contemporary European design 19.6cf (14cf fridge, and 5.6cf freezer)

90-degree opening flush hinges

Large and accessible digital display Soft close crisper and pantry drawer

Refrigerator adjustable temp from +35°F (2°C) to +46°F (8°C)

Chiller Zone adjustable temp from +30°F (-1°C) to +41°F (5°C)

Freezer adjustable temp from +5°F (-15°C) to -11°F (-24°C).

Sabbath mode, Holiday mode, ECO mode

Height adjustable cantilever shelves

Spill-proof glass shelves

LED lighting

French door design

3D door adjustment for easy panel alignment

Ultra quite 41 dB(A)


Appliance leveling from the front and rear


Interior filtered water dispenser

fulgor-milano.us FULGOR MILANO

36" FRENCH DOOR PANEL READY FRIDGE

PANEL READY FRENCH DOOR REFRIGERATOR





CODE ID	36" FRENCH DOOR PANEL READY FRIDGE FM4FBM36IFBI
Finish	Panel Ready
PERFORMANCE/CAPACITY	
Cooling System	Frost Free
Control System	Electronic
Energy Star Qualified	Yes
Refrigerant	R600A
Noise Level dB(A)	41
Total Net Volume, cu. ft. (Liters)	19.6 (555)
Fresh Food Net Volume, cu. ft. (Liters)	14 (396)
Freezer Net Volume, cu. ft. (Liters)	5.6 (159)
FEATURES	
Fridge Compartment	
Interior Filtered Water Dispenser	Yes
Control Display	Digital
Automatic Defrost	Yes
Interior Lighting	LED
Spill-proof Shelves	3
Crispers	1
Door Bins	3
Compressor	Inverter Fixed Frequency
Fan Assisted Cooling	Yes
Freezer Compartment	
Automatic Defrost	Yes
Freezer Drawers	1
Ice Maker	Yes
DIMENSIONS / WEIGHT	
Width in. (mm)	35-3/4 (908)
Height in. (mm)	83-9/16 (2123)
Depth in. (mm)	23-5/16 (592)
Product Weight lbs. (kg)	355 (161)
RECOMMENDED PANEL DIMENSIONS	
Fridge Panels	
Height, in. (mm)	51-1/16 (1297)
Width, in. (mm)	17-11/16 (449)
Thickness*, in. (mm)	3/4 (19)
Max. Weight, lbs. (kg)	35.7 (16.2)
Freezer Panel	
Height, in. (mm)	28-11/16 (729)
Width, in. (mm)	35-3/4 (908)
Thickness, in. (mm)	3/4 (19)
Max. Weight, lbs. (kg)	19.8 (9)
POWER / RATINGS	
Dedicated Circuit, V/Amps	120 V - 15 A
Supply voltage, V/Hz	120 V - 60 Hz
Rated Current, Amps	3.0 A

*Fridge Panels with a greater thickness of 1-1/2 in. (38mm) require the use of a 90-degree hinge limiting pin.