

7 SERIES INTEGRATED 36"W. ALL REFRIGERATOR

Viking 7 Series - FRI

GOOD FOR YOUR FOOD, EVEN BETTER FOR YOUR HEALTH

- EXCLUSIVE BlueZone[™] Fresh Preservation Technology is a unique, patented air cleaning technology that strips microbes, ethylene gas, hydrocarbons, and odors from the air
 - Significantly extends food shelf life, quality, and flavor
 - Slows ripening, reduces mold, and eliminates odors
 - Commercial technology now for residential use
 - The patented BlueZone blub will last about 12 months which is about 8,000 hours of use and a indicator light will appear when it is time to replace

DESIGN FEATURES

- Proprietary Fully Articulating Hinge has three dimensional adjustability for a perfect fit in integrated installations, and the hinge damper allows for smoothness when opening and closing door
- Capacitive Touch Controls with intuitive user interface
- Brilliant Led Lighting ensures all items are in clear view with bright, energy efficient, ramp-on theater LED lighting from top and sidewalls
- Three separate crisper drawers offer dedicated area for produce/meats
- Three adjustable seamless glass shelves make cleanup easy and maximize usable space

PRO CHILL[™] TEMPERATURE MANAGEMENT SYSTEM

- Variable-Speed High-Efficiency Overdrive[™] Compressor quickly chills food and saves energy
- One of the quietest, most technologically advanced compressors available with electronic controls
- Maintains temperature to within 1°F to keep food fresher longer
- Compressor located on the bottom allowing for full integration of the product



Shown with optional stainless steel door panel kit

FEATHER TOUCH[™] INTERNAL WATER DISPENSER

Dispenses filtered water with a single touch

MODEL NUMBERS

 FRI7360W(R/L) – 36"W. All Refrigerator accepts wood panel or optional stainless steel/color door panel

ACCESSORIES

- VICDP36** door panel kit with handle
- RWFDISP Replacement water filter
- RBZB7VT BlueZone replacement kit
- PHK528-SS Professional Stainless Steel handle (1 piece/28")
- CKVBIWH Connector kit (for use when installing two units side by side)

DESIGN OPTIONS

Order as right or left mounted hinge

DOOR PANEL COLOR FINISHES

- Stainless Steel (SS)
- Volume 1 Color Finishes include Antique Bronze (AN), Blush (BH), Cast Black(CS), Damascus Gray (DG), Eucalyptus (EU), Ivy (IV), Martini (MA), November Sky (NS), Slate Blue (SB), Spiced Cider (SC), Splash (SP)
- Volume 2 Color Finishes include Daffodil (DA), Golden Hour (GH), Nantucket (NA), Onyx (ON), Pure White (PW), Squall (SQ), Valentine (VA)

WARRANTY

- 2-year full covers complete unit
- 6-year full sealed refrigeration system
- 90-day full cosmetic parts such as glass, painted items, and decorative items
- 12-year limited sealed refrigeration system



7 SERIES INTEGRATED 36"W. ALL REFRIGERATOR

Viking 7 Series - FRI

36" INTEGRATED ALL REFRIGERATOR			
DESCRIPTION	FRI7360 (WITH OPTIONAL DOOR PANEL)		FRI7360 (WITH CUSTOM PANEL)
Overall Width	36" (91.4 cm)		
Overall Height (from bottom)	83-15/16" (213.2 cm) min to 84-3/4" (215.7 cm) max		
Overall Depth from rear	To front edge kickplate: 22-1/16" (56.0 cm) To front of door panel: 24-3/4" (62.9 cm)		To front edge kickplate: 22-1/16" (56.0 cm) To front of door panel: 24" (61.0 cm)
	To front of handle endcap: 27-11/16" (70.3 cm)	To front of handle endcap: 27-5/16" (69.4 cm)	
Cutout Width	36" (91.4 cm)		
Cutout Height	84" (213.4 cm) min to 85-3/16" (216.3 cm) max		
Cutout Depth	25" (63.5 cm) min.		
Electrical Requirements	115 volt, 60 Hz, 15 amp dedicated circuit; 3-wire cord with grounded 3-prong plug attached to product		
Maximum Amp Usage	9.9 amps		
Inlet Water Requirements	1/4" copper tubing inlet waterline; minimum 20 psi; maximum 120 psi		
Overall Interior Capacity	20.4 cu. ft.		
Approximate Shipping Weight	517 lbs. (234.5 kg)		

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2023 Viking Range, LLC All rights reserved. Specifications subject to change without notice.