## SUMMIT

# SBC7BRSFLTWCFADA



32" x 23.63" x 22.38" (H x W x D)

Built-in 24" wide dual tap cold brew coffee dispenser with a removable tap system for non-permanent installation

#### **Highlights:**

Innovative Floating Tap lets you create a complete undercounter kegerator without modifying your countertop

Easy-to-install + removable tap system allows you to change your space as needed

Built-in coffee kegerator for undercounter installation

#### **Product Features:**

24" Wide Built-In Floating Tap Coffee Dispenser	Dual tap kegerator with a remote tapping system that includes everything you need to pour draft cold brew without modifying your countertop	
Patent pending commitment-free design	Non-permanent draft tower is separated from the actual kegerator and designed for temporary installation on counter surfaces, allowing you to remove as needed	
Built-in capable	Designed for installation under the counter	
No drilling needed	Tower is connected to the removable tap kit that does not need to be permanently attached to your countertop	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Easy installation	No tools or equipment needed for fast setup and easy removal	
Convertible to a refrigerator	Includes a tap hole cover, glass shelves, and a scalloped steel bottle rack to all you to convert the kegerator into a traditional all-refrigerator	
Versatile use	Approved for both residential and commercial settings	
Fits under standard counters	Floating tap kit requires 2 1/4" between the top of the kegerator and bottom of the counter in order to fit the keg's tubing	



### **SBC7BRSFLTWCFADA Specifications:**

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	31.88" (81 cm)		
Height to Hinge Cap	32.0" (81 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Depth	22.38" (57 cm)		
Depth with Handle	24.3" (62 cm)		
Depth with door at 90°	44.5" (113 cm)		
Capacity	5.8 cu.ft. (164 L)		
Defrost Type	Automatic		
Door	Stainless Steel		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Energy Usage/Year	239.0kWh/year		
Amps	0.8		
Voltage/Frequency	115 V AC/60 Hz		
Weight	180.0 lbs. (82 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101145563		
Kegerator			
Door Swing	RHD		
Reversible	Yes		
Height Adjustable	No		
Tap Kit	Yes		
Number of Taps	2		
Adjustable Shelves	Yes		
Shelf Type	Glass and Scalloped		
Shelf Qty	4		
Thermostat Type	Dial		
Interior Light	Yes		
Refrigerant	R600a		
Refrigerant Amount	0.64 oz.		
Inter Height	27.0" (69 cm)		
Interior Width	21.0" (53 cm)		

Interior Depth	17.75" (45 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Level Legs Qty	4
Temperature Range	36 to 46°F





