


Euro Pro Wall Mount Hood with Emerald-Cut Edges, Magic Lung® Blower

This European-style hood creates a refined silhouette, pairing linear styling with our patented emerald lip featuring soft-cut corners. Patented Magic Lung® technology delivers powerful yet exceptionally quiet ventilation through centrifugal filtration, while SensaSource® automatically adjusts blower speed for enhanced grease control and fire safety. Dishwasher-safe components simplify cleanup. Matching duct covers sold separately.


To view available finishes & accessories please visit ventahood.com/products/SEPH18-236

SPECIFICATIONS

WIDTH	36"
DEPTH	24"
HEIGHT	18"
CFM ¹	600
EQUIVALENT CFM ²	900
SOUND RATING (HIGH SPEED) ³	6.5 Sones / 57 dB
LIGHTING ⁴	2 LEDs 2700K Warm White




DUCT COVERS





Wall Mount Duct Cover
Models: WDCRND-12/12, WDCRND-12/24, WDCRND-12/36

RECOMMENDED MOUNTING HEIGHT



NOTE: Exceeding recommended mounting height may compromise performance.

CONNECTIONS



ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT

MODEL	VOLTS	AMPS	HZ	RPM	CFM @ 0.0" SP ⁵	CFM @ 0.1" SP	CFM @ 0.2" SP	CFM @ 0.3" SP	MIN. ROUND DUCT SIZE
B200 Dual	115	4.0	60	1550	600	531	480	430	8" (50sq.in.)

¹ CFM (cubic feet per minute) measures airflow. ² Because Magic Lung® blowers use centrifugal filtration instead of traditional baffle or mesh filters, they move air more efficiently. When comparing to other brands, use Equivalent CFM to understand real-world performance. ³ Sones measure perceived loudness—lower values indicate quieter operation. Decibel values shown are approximate equivalents. ⁴ This model is not available with heat lamps. ⁵ Airflow (CFM) decreases as duct resistance (static pressure) increases. Values at 0.1"–0.3" SP reflect typical installed conditions.