



30 in. Wall Mount Chimney Range Hood

SHC3043SNS

- 3-Speed + Boost Stainless Steel Hood
- 400 CFM Blower for Fast Ventilation
- Premium LED Task Lighting
- Convertible to Ductless Venting with Optional Ductless Kit
- Dishwasher-Safe Mesh Grease Filters

STYLE & DESIGN

Finish	Stainless Steel
Width	30"
Type of Control	Electronics

FEATURES

Speed Levels	3 Levels + Boost
Max. Blower CFM*	400 CFM
Boost Mode	6 minutes
Sones Sound Level	6.0
Grease Filters	2 Aluminum Filters
	Dishwasher safe
Lighting	5W LED x 2 3000K
Light Levels	On/Off
Recirculation	Yes, with Optional Ductless Kit
Diameter Air Outlet	6" round
Flues Options	Yes, 38-9/16" to 64-5/16" long

MOUNTING HEIGHT

For Electric Range	Minimum 24" from cooktop to bottom of hood
For Gas Range	Minimum 30" from cooktop to bottom of hood

ADDITIONAL SPECIFICATIONS

AC Power	120V 60Hz 2.4Amps
Safety Regulation	UL
AHAM Verified	Yes

OPTIONAL ACCESSORIES

NAME	MODEL #	UPC
Ductless Conversion Kit	SKCH63DLK	074000623156
Charcoal Filter Replacement	SKCH63CFL	074000623163
Extension Flue	SKCH63EXT	074000623170
Remote Control Unit	SKCH63RHU	074000623187

DIMENSIONS & WEIGHT (IN./LBS.) (W x H x D)

Product Dimensions	29-15/16" x 34-11/16" x 18-1/2"
Shipping Dimensions	32-11/16" x 13-9/16" x 22-13/16"
Product Weight/Shipping Weight	22.0 lbs. / 27.3 lbs.

WARRANTY/UPC

Parts	1 Year Limited
Labor	1 Year Limited
UPC	074000623118

*Max. blower CFM indicates the performance of the hood blower in open air and is not HVI certified.

PRODUCT DIMENSIONS

The following are measurements only. Do not use to install the wall mount chimney range hood. For detailed installation instructions, please refer to the installation manual.

