



36 in. Wall Mount Chimney Range Hood

SHC3663SNS

- 3-Speed + Boost Stainless Steel Hood
- 600 CFM Blower for Fast Ventilation
- Adjustable CFM Ventilation Tailors Airflow to Your Kitchen
- Premium LED Task Lighting
- 15-Minute Delay Off Timer
- ADA Compliant with Optional Remote Hand Unit
- Convertible to Ductless Venting with Optional Ductless Kit
- Dishwasher-Safe Mesh Grease Filters

STYLE & DESIGN

Finish	Stainless Steel
Width	36"
Type of Control	Electronics with Backlight

FEATURES

CFM Adjustable Platform (CAP)	Yes
Speed Levels	3 Levels + Boost
Max. Blower CFM*	600 CFM
Boost Mode	10 minutes
Sones Sound Level	7.5
Auto Delay Off	15 minutes
Grease Filters	3 Aluminum Filters
	Dishwasher safe
Lighting	5W LED x 2 3000K
Light Levels	On/Off
Recirculation	Yes, with Optional Ductless Kit
Diameter Air Outlet	6" round
Flues Options	Yes, 38-9/16" to 64-5/16" long

MOUNTING HEIGHT

For Electric Range	Minimum 24" from cooktop to bottom of hood
For Gas Range	Minimum 30" from cooktop to bottom of hood

ADDITIONAL SPECIFICATIONS

AC Power	120V 60Hz 3.3Amps
ADA Compliant	Yes, With Optional Remote Unit
Safety Regulation	UL
AHAM Verified	Yes

OPTIONAL ACCESSORIES

NAME	MODEL #	UPC
Ductless Conversion Kit	SKCH63DLK	074000623156
Charcoal Filter Replacement	SKCH63CFL	074000623163
Extension Flue	SKCH63EXT	074000623170
Remote Control Unit	SKCH63RHU	074000623187

DIMENSIONS & WEIGHT (IN./LBS.) (W x H x D)

Product Dimensions	35-3/8" x 34-11/16" x 18-1/2"
Shipping Dimensions	38-3/16" x 13-9/16" x 22-13/16"
Product Weight/Shipping Weight	24.9 lbs. / 30.4 lbs.

WARRANTY/UPC

Parts	1 Year Limited
Labor	1 Year Limited
UPC	074000623149

*Max. blower CFM indicates the performance of the hood blower in open air and is not HVI certified.

PRODUCT DIMENSIONS

The following are measurements only. Do not use to install the wall mount chimney range hood. For detailed installation instructions, please refer to the installation manual.

