PREP FOR CARD

STACKED WASHER-DRYERS



Prep for Card

Prep for card payment actuations involve integrating a secure and robust digital payment platform. This enhances the customer experience, streamlines transactions, and boosts operational efficiency.

Stacked Washer-Dryers *(Tall)*

- Washer is ADA compliant
- Combines heavy-duty construction with reliable operation
- The freestanding softmount design can be installed on all floor types or levels



ENERGY STAR®
Certified Washer



Prep for Card – Stacked Washer-Dryer Control Panel

COMMERCIAL THROUGH RETAIL

PREP FOR CARD
STACKED
WASHER-DRYERS



Product		Stacked Washer-Dryer	
		Washer	Dryer
Color		White	
Capacity - lb (kg)		21.5 (9.5)	18 (8.2)
Cylinder Volume - cu.ft. (liters)		3.42 (96.8)	7.0 (198)
Spin Speed G-Force (RPM)		440 (1200)	–
Motor Size - HP		0.9	0.33
Type of Gas (Gas Models Only)		–	Factory Equipped Natural
Water Consumption Per Cycle - g (liter)*		13.68 (51.8)	–
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*		4.0 (0.53)	–
MEF_{J2} (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*		2.20 (62.3)	–
Available Cycles		Normal, Synthetic, Delicate	High, Medium, Low, Delicate, No Heat
Air Outlet Diameter - in		–	4
Exhaust Airflow - cfm (liters/sec)		–	220 (105)
Electrical Requirements (v/Hz/Ph-Amp)	**Electric	120/60/1-15 Amp	208-240/60/1-30 Amp
	Gas	120/60/1-15 Amp	
Heating Element	Electric	–	5350W, 240V / 4750W, 208V
	Gas	–	25,000 Btu
Net Weight - lb (kg)		385 (175)	
Shipping Weight - lb (kg)		417 (189)	
Shipping Dimensions Approx. - in	Width	34	
	Depth	30	
	Height	80	
Agency Approvals	Electric	cULus	
	Gas	cCSAus	
Model No.		STENYASP178TW01, STGNYASP118TW01	

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Stacked Washer-Dryer - Tall	26.875	78.17	28	14.6***	24

Note *(not supplied)*: Stacked washer-dryer requires two power cords, one for washer, one for dryer.

For Commercial Use Only

* Average usage based on multiple load sizes and current DOE test protocol.
Real usage will vary depending on load size, composition and cycle selectivity.

** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

*** For ADA compliance turn legs out from base 0.5 inches.

For additional accessories and warranty, please refer to the price list.