accucold

URM19W

72" x 30.5" x 27.63" (H x W x D)

Upright manual defrost refrigerator with lock and external alarm/thermometer for general purpose storage applications

Highlights:

General purpose refrigerator designed for the storage of samples, enzymes, reagents, and other laboratory and clinical materials that require a more stable interior than traditional automatic defrost

Static cooling system with manual defrost to ensure a more stable interior

Factory-installed lock provides security you can count on

Product Features:

Upright All-Refrigerator	Large capacity refrigerator with front-opening design and manual defrost operation
Large capacity	More than 18 cu.ft. of interior space
Manual defrost	Static cooling system with no fans or warming cycles
Dial thermostat	Intuitive and reliable mechanical thermostat located inside the unit to prevent unnecessary adjustments
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents
Access port	3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user-provided monitoring equipment
Cantilevered shelving	Tight pilaster spacing throughout the interior allows you to adjust the shelf positions to meet your exact storage needs

accucold

URM19W Specifications:

Overview	
Nominal Height	72.0" (183 cm)
Height of Cabinet	72.0" (183 cm)
Nominal Width	31.0" (79 cm)
Width	30.5" (77 cm)
Nominal Depth	28.0" (71 cm)
Depth	27.63" (70 cm)
Depth with Handle	30.25" (77 cm)
Depth with door at 90°	55.38" (141 cm)
Capacity	18.3 cu.ft. (518 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	2.7
Voltage/Frequency	115 V AC/60 Hz
Weight	215.0 lbs. (98 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106762
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	4
Full Door Shelf Qty	4
Thermostat Type	Dial
Refrigerant Type	R290
Refrigerant Amount	3.88oz.
High Side PSI	280.0
Low Side PSI	145.0
Interior Light	Yes
Temperature Range	1 to 10ºC
Sound Level	32.3 dB
Dimensions	
Interior Height	64.0" (163 cm)

Interior Width	25.25" (64 cm)
Interior Depth	21.0" (53 cm)
Compressor Step Height	9.25" (23 cm)
Compressor Step Width	25.25" (64 cm)
Compressor Step Depth	7.25" (18 cm)





SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**