



Easily vent smoke and odors with this 300 CFM Motor Class MHC that comes equipped with a hood fan for powerful ventilation. This 30" MHC also comes with a detachable grease filter for convenient cleaning and halogen cooktop lighting.

HOOD PERFORMANCE

Duct Orientation	Size	Damper	Sones		CFM*		
			Low	High	Low	High (0.1 in.w.g.)	High (0.25 in.w.g.)
Vertical	10x3.25 in.	Included	1.4	5.1	114.5	217.9	201.3
Horizontal	10x3.25 in.	Included	1.7	5.0	105.7	154.5	126

FEATURES

Motor class CFM**	300 CFM
Lighting	Single halogen lamp
Hood speed	3
Grease filter	Aluminum (Qty.1)
Charcoal filter	Charcoal (QTY.1)
Venting	Exhaust or Recirculation
Energy star	No

AC INPUT

120V, 60HZ


MOUNTING HEIGHT

From cooktop to the bottom of MHC
12 1/8" (Minimum) - 18 1/8" (Recommend)

LIMITED WARRANTY


1 year limited warranty (See manual for full detail)

FOR INDOOR USE ONLY




- A. 29 7/8" (76.1 cm)
- B. 17 1/8" (45.4 cm)
- C. 12 1/8" (31.3 cm)

HS Vertical



HS Horizontal



*When configured for outside ventilation. Independently tested through the AHAM Verified program.

** Max. blower CFM indicates the performance of the hood blower in open air.

***Recommended to use a rectangular duct (3.25" x 10") or a round duct (6") to help achieve better airflow performance. Different duct sizes and transitions can have different back pressure and get different airflow performance. Shorter duct length and fewer transitions can help achieve better airflow performance.

For questions about features, operation/performance, parts, accessories or service, call: 1-866-698-2538 or visit our website at www.whirlpool.com In Canada, call 1-800-807-6777 or visit our website at www.whirlpool.ca